



**CARPET & FLOOR TILE PURCHASE,
INSTALLATION, REMOVAL AND REPAIR
BID # 09-0231**

Date: 11/18/2009 Addendum: #01 Due Date: 12/03/2009

The purpose of this addendum is to incorporate the following changes into the purchase specification.

1. **BID DUE DATE:**
 - a. **Bid due date has been extended to 12/03/2009. Bids are still due no later than 1:30 p.m. Bids will be opened at 2:00 p.m. in council chambers.**

2. **Section 4.0 Vinyl Floor Tile has been changed. See below and New Bid Specs posted on website.**

- 3.0 **VINYL FLOOR TILE – AZROCK ***REVISED*** REVISED*****
 - 3.1 **MATERIALS**
 - A. Vinyl Composition Tile Manufacturer: Azrock by Tarkett Commercial, Telephone 800-558-2240 (samples) and 800-366-2689 ext. 2706 (Tarkett Commercial Technical Assistance); Fax 713-869-5271 (TarkettCommercial Technical Assistance). E-mail Technical Assistance: AzTech@Tarkett.com
 - B. Standards: Meet or exceed requirements of ASTM F 1066, Class 1 or 2, non-asbestos formulated
 - C. Quality Assurance: Product manufacturing facility to be compliant with latest ISO 9000 Standard [for shipboard application manufacturing facility and product to be IMO Compliant].
 - D. Manufacturers recommended adhesive to contain no regulated VOC's.
 - E. Size: 12 inch by 12 inch
 - F. Gauge: 1/8 [3/32] inch.
 - G. Flammability: Provide materials with 1.0 CRF (critical radiant flux) or higher when tested in accordance with ASTM E 648, Flooring Radiant Panel Test.
 - H. Provide materials with smoke density of less than 450 when tested in accordance with ASTM E 662.
 - I. Static Load: Provide materials with static load limit of 150 psi or higher.
 - J. Slip Resistance: Provide materials with minimum rating for floors of > 0.60.

- K. Color and Pattern: As selected by Architect from manufacturer's full range of available colors and patterns, including Standard (Class 2) and Premium (Class 1, and 2).
 - a. Standard Pattern, Class 2, Cortina Colors & Classics (65 colors).
 - b. Premium Pattern, Class 1, Solids (14 colors)
 - c. Premium Pattern, Class 2, Thru-Quartz (12 colors)
 - d. Premium Pattern, Class 1, Feature Strip (14 colors) [1/4", 1/2", 1", 2", 4", 6" by 24" sizes available]
 - e. Premium Pattern, Class 2, Granite (7 colors).
 - f. Premium Pattern, Class 2, Granite Slip Resistant (8 colors); slip resistance rating of 0.8.
- L. Edge Strips (Moldings): Homogeneous vinyl, tapered or bullnose edge. Color: as selected by Architect to compliment vinyl composition tile.
- M. Subfloor Filler: Hydraulic/Portland cement based material designed for providing thin solid surface for leveling and for minor ramping of subsurface to adjacent floor finishes. Use material capable of being applied and feathered out to adjacent floor without spalling.
- N. Primers and Adhesives: Water and alkali resistant, zero regulated VOC types as recommended by flooring manufacturer for specific application.
- O. Floor Finish: Finish as recommended by flooring manufacturer for material type and location.

*** END REVISED SECTION *** END REVISED SECTION *** END REVISED SECTION***

ALL OTHER TERMS AND CONDITIONS REMAIN UNCHANGED

Yours Truly,

**Jack Dale,
Purchasing Manager**

ACKNOWLEDGMENT

By the signatures affixed below, **Addendum No. 01** is hereby incorporated into and made part of the above referenced Invitation to Bid.

Receipt Acknowledged By:

Company Name	Authorized Signature	Date

NOTE: Company name and signature must be the same as on the original bid. Return original to the Purchasing Division, City of Fort Worth, Texas prior to submittal or with your sealed bid. FAILURE TO DO SO MAY CONSTITUTE GROUNDS FOR REJECTION OF YOUR OFFER.